



05000EF Motor Oil 5W-30 Premium Synthetic C1 Mazda / Jaguar

Document version: May 20, 2024



Description

This premium synthetic top quality 'Low SAPS' Long Life motor oil has been specially developed for petrol and diesel engines where SAE 5W-30 with ACEA C1 standard is required and equipped with an exhaust gas after-treatment system. This motor oil is recommended for various cars such as Mazda, Jaguar and Land Rover.

According to the specifications of

ACEA C1
Ford WSS-M2C934-B
JASO DL-1
Jaguar/Land Rover STJLR.03.5005
Mazda Service Fill

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001EF	1 L	6	450
05005EF	5 L	4	112
05020EF	20 L	1	30
05060EF	60 L	1	6
05205EF	205 L	1	2
05999EF	1000 L	1	-
P05000EF	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.848	kg/l	
Viscosity	5W-30		
Kinematic Viscosity at 40°C	55.6	mm ² /s	
Kinematic Viscosity at 100°C	10	mm ² /s	
Viscosity Index	169		
Dynamic Viscosity at -30°C	4000	mPa.s	
Flashpoint COC	226	°C	
Pourpoint	-36	°C	
Total Base Number	7.8	mgKOH/g	
Sulphated Ash	0.5	mass%	
High Temperature High Share	2.9	mPa.s	

These characteristics are typical of current production. Variations in these characteristics may occur.