



16000 ATF Automatic Transmission Fluid Dexron III F/G

Document version: May 18, 2024



Description

This premium synthetic ATF Dexron III F/G automatic transmission oil has been specially developed for automatic transmissions, power steering, torque converters and other applications for which manufacturers specify an ATF Dexron III F/G oil.

Application manual

According to the specifications of

Allison C4
Fiat 9.55550-AG2
Ford ESP-M2C138-CJ / ESP-M2C166-H / M2C186-A / Mercon
GM Dexron III F / Dexron III G
MAN 339 Type V1 / 339 Type Z1
MB 236.9
Nissan ECVT
Voith H55.6335xx
Volvo STD 1273.41 (97341)
ZF TE-ML 03D / 04D / 09 / 11B / 14A / 17C

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001	1 L	6	450
16004	4 L	4	112
16020	20 L	1	30
16060	60 L	1	12
16205	205 L	1	2
16999	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density	0.850	kg/l
Colour	red	
Viscosity	10W	
Kinematic Viscosity	7.7	mm ² /s
Viscosity Index	205	
Flashpoint	196	°C
Pourpoint	-45	°C
Brookfield Viscosity	18400	mPa.s

These characteristics are typical of current production. Variations in these characteristics may occur.