



16000LV Automatic Transmission Fluid LV

Document version: May 20, 2024



Description

This premium synthetic 'Low Viscosity' automatic transmission oil with very good thermal and oxidation stability. The high quality base oil with a well-balanced additive package provides reduced friction properties and optimal shifting performance. This automatic transmission oil provides excellent fuel economy.

According to the specifications of

Aisin Warner JWS 3324
Ford Mercon LV / WSS-M2C938-A
Honda DW-1
Mitsubishi Dia Queen ATF J3 / Dia Queen ATF-PA
Toyota Fluid WS
VW G 055 540

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001LV	1 L	6	450
16004LV	4 L	4	112
16020LV	20 L	1	30
16060LV	60 L	1	6
16205LV	205 L	1	2
16999LV	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.847	kg/l	ASTM D4052
Colour	red		
Kinematic Viscosity at 40°C	29.4	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	6.1	mm ² /s	ASTM D445
Viscosity Index	162		ASTM D92
Dynamic Viscosity at -20°C	9500	mPa.s	ASTM D5293
Flashpoint COC	210	°C	ASTM D92
Pourpoint	-45	°C	ASTM D97

These characteristics are typical of current production. Variations in these characteristics may occur.