



# 16000HFM ATF Automatic Transmission Fluid HFM

Document version: May 18, 2024



## Description

This premium synthetic automatic transmission oil has been specially developed for all Audi, VW, Porsche, Volvo, Toyota, Lexus and Saab models (amongst others) fitted with an Aisin Warner automatic transmission.

## According to the specifications of

Aisin Warner JWS 3309 / JWS 3314 / JWS 3317  
BMW ETL-7045E / ETL-8072B  
Fiat 9.55550-AV1  
Ford Mercon-V / WSS-M2C202-B  
Honda ATF Z1  
Hyundai ATF SP-III / ATF SP-IV  
KIA SP-III / SP-IV  
Mitsubishi Diamond SP-II / Diamond SP-III  
Nissan Matic D / Matic J / Matic K  
Opel/GM 1940 773  
Saab JWS 3309  
Suzuki JWS 3309  
Toyota T / T-III / T-IV  
VW G 055 025  
Volvo 1161540

## Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001HFM	1 L	6	450
16004HFM	4 L	4	112
16020HFM	20 L	1	30
16060HFM	60 L	1	6
16205HFM	205 L	1	2
16999HFM	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.849	kg/l	
Colour	red		
Viscosity	10W		
Kinematic Viscosity at 40°C	35.6	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	8.1	mm <sup>2</sup> /s	
Viscosity Index	212		
Brookfield Viscosity at -40°C	12000	mPa.s	

These characteristics are typical of current production. Variations in these characteristics may occur.