



16000HT Automatic Transmission Fluid High Torque

Document version: May 18, 2024



Description

This automatic transmission fluid has been specially designed for modern Aisin Warner transmissions with AW-1 recommendation and in Jatco transmissions. Thanks to the well balanced additive package, this automatic transmission fluid has excellent friction properties and shifting performance. This liquid also has durable anti-shudder properties.

According to the specifications of

Aisin Warner AW-1
Fiat 9.55550-AV2
Ford M2C922-A1
JATCO 3100 PL085 / FWD (N402) / JF506E (K17)
VW G 052 990

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001HT	1 L	6	450
16004HT	4 L	4	112
16020HT	20 L	1	30
16060HT	60 L	1	6
16205HT	205 L	1	2
16999HT	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.849	kg/l
Colour	Red	
Kinematic Viscosity at 40°C	32.7	mm ² /s
Kinematic Viscosity at 100°C	7.02	mm ² /s
Viscosity Index	184	
Dynamic Viscosity at -40°C	12000	mPa.s
Flashpoint COC	218	°C
Pourpoint	-48	°C

These characteristics are typical of current production. Variations in these characteristics may occur.