



39000F Industrial Gear Oil 320

Document version: May 20, 2024



Description

This mineral industrial gearbox oil 320 has been specially developed for use in sealed gearboxes, equipped with straight, spiral, conical and worm gears.

According to the specifications of

AGMA 9005-E02
AISE 224
DAVID BROWN S1.53.101E
DIN 51517 part 3 CLP

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 39001F | 1 L | 6 | 450 |
| 39005F | 5 L | 4 | 112 |
| 39020F | 20 L | 1 | 30 |
| 39060F | 60 L | 1 | 6 |
| 39205F | 205 L | 1 | 2 |
| 39999F | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|------------|--------------------|
| Density at 15°C | 0.9 | kg/l |
| Viscosity | ISO VG 320 | |
| Kinematic Viscosity at 40°C | 330 | mm ² /s |
| Kinematic Viscosity at 100°C | 24.2 | mm ² /s |
| Viscosity Index | 94 | |
| Flashpoint COC | 255 | °C |
| Pourpoint | -21 | °C |
| Total Acid Number | 0.38 | mgKOH/g |
| FZG A/16,6/140 | 12 | level |

These characteristics are typical of current production. Variations in these characteristics may occur.