



## 02000 Motor Oil 15W-40 Turbo Universal

Document version: 18 May 2024



### Description

This universal mineral motor oil has been specially developed for normal duty petrol engines and diesel engines of cars. This motor oil is also suitable for turbo diesel engines.

### Application manual

According to the specifications of

ACEA A3/B4 / E2  
API CG-4 / SL  
Allison C4  
Caterpillar TO-2  
MAN M 271  
MB 228.1  
Volvo VDS

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 02001    | 1 L    | 6              | 450              |
| 02004    | 4 L    | 4              | 112              |
| 02005    | 5 L    | 4              | 112              |
| 02020    | 20 L   | 1              | 30               |
| 02060    | 60 L   | 1              | 6                |
| 02205    | 205 L  | 1              | 2                |
| 02999    | 1000 L | 1              | -                |
| P02000   | 1 L    | 1              | -                |

## Standard analyses

| TEST                         | VALUE  | METHOD             |
|------------------------------|--------|--------------------|
| Density at 15°C              | 0.873  | kg/l               |
| Viscosity                    | 15W-40 |                    |
| Kinematic Viscosity at 40°C  | 90.5   | mm <sup>2</sup> /s |
| Kinematic Viscosity at 100°C | 13.5   | mm <sup>2</sup> /s |
| Viscosity Index              | 151    |                    |
| Flashpoint COC               | 200    | °C                 |
| Pourpoint                    | -30    | °C                 |
| Total Base Number            | 8.4    | mgKOH/g            |
| Sulphated Ash                | 1      | mass%              |

These characteristics are typical of current production. Variations in these characteristics may occur.