



BL032000 Marine Engine Oil Multi Grade 15W-40

Document version: 18 May 2024



Description

This universal mineral marine engine oil is specially suitable for use in the first generation normal duty petrol engines and diesel engines with or without turbocharged.

According to the specifications of

API CG-4
Allison C4
Caterpillar TO-2
Cummins
DAF
Deutz/MWM
Lister
MAN M 271
MB-Approval 228.1
Vetus
Volvo VDS
Yanmar

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| BL032001 | 1 L | 6 | 450 |
| BL032005 | 5 L | 4 | 112 |
| BL032020 | 20 L | 1 | 30 |
| BL032060 | 60 L | 1 | 6 |
| BL032205 | 205 L | 1 | 2 |
| BL032999 | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|--------|--------------------|--------|
| Density at 15°C | 0.883 | kg/l | |
| Viscosity | 15W-40 | | |
| SAE | 15W-40 | | |
| Kinematic Viscosity at 40°C | 107 | mm ² /s | |
| Kinematic Viscosity at 100°C | 14 | mm ² /s | |
| Viscosity Index | 132 | | |
| Flashpoint COC | 228 | °C | |
| Pourpoint | -30 | °C | |
| Total Base Number | 6.1 | mgKOH/g | |
| Sulphated Ash | 1 | mass% | |

These characteristics are typical of current production. Variations in these characteristics may occur.