



## 41000A Motor Oil SAE 10 Super Single Grade

Document version: May 20, 2024



### Description

This mineral SAE 10 Super Single Grade oil has been developed for a wide range of purposes and is extremely suitable for stationary engines, for industrial transmissions and for hydraulic systems.

### According to the specifications of

ACEA E2  
API CF-4 / SG  
Caterpillar TO-2  
MAN 270  
MB 227.0 / 228.0  
MIL-L-2104E  
MIL-L-46152E  
ZF TE-ML 03B / 05K

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 41001A   | 1 L    | 6              | 450              |
| 41005A   | 5 L    | 4              | 112              |
| 41020A   | 20 L   | 1              | 30               |
| 41060A   | 60 L   | 1              | 6                |
| 41205A   | 205 L  | 1              | 2                |
| 41999A   | 1000 L | 1              | -                |
| P41000A  | 1 L    | 1              | -                |

## Standard analyses

| TEST                         | VALUE |                    | METHOD |
|------------------------------|-------|--------------------|--------|
| Density at 15°C              | 0.875 | kg/l               |        |
| Viscosity                    | 10W   |                    |        |
| Kinematic Viscosity at 40°C  | 41    | mm <sup>2</sup> /s |        |
| Kinematic Viscosity at 100°C | 6.7   | mm <sup>2</sup> /s |        |
| Viscosity Index              | 118   |                    |        |
| Flashpoint COC               | 212   | °C                 |        |
| Pourpoint                    | -39   | °C                 |        |
| Total Base Number            | 7.0   | mgKOH/g            |        |
| Sulphated Ash                | 0.88  | mass%              |        |

These characteristics are typical of current production. Variations in these characteristics may occur.