



## 86000A Antifreeze Premium Longlife G12+ Concentrate

Document version: May 20, 2024



### Description

This Long Life OAT silicate-free antifreeze is of very high quality and has been specially developed for protection of non-ferrous metals such as aluminium and magnesium. This antifreeze should be diluted with the recommended quantity of water before use.

### According to the specifications of

ASTM D3306  
DAF 74002  
Ford ESE-M97B49-A / WSS-M97B44-C / WSS-M97B44-D  
GM/Opel 1940 656 / 6277M  
MAN 248 / 324 SNF  
MB 325.3  
Paccar 74002  
Renault 41-01-001  
VW TL 774D G12+ / 774F G12+  
Volvo No. 260 / VCS

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
86001A	1 L	6	450
86005A	5 L	4	112
86020A	20 L	1	30
86060A	60 L	1	6
86205A	205 L	1	2
86999A	1000 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 20°C	1.12	kg/l
Colour	red	
Freezing Point 50% diluted	-40	°C
Ph 50% diluted	7.6	
Water	3.72	mass%
Copper Corrosion	5.3	

These characteristics are typical of current production. Variations in these characteristics may occur.