



BL022000 Marine FC-W Engine Oil 4-Stroke Inboard 25W-40

Document version: May 18, 2024



Description

The marine 4T Inboard / Outboard Oil is a four stroke engine oil based on high quality base oils with special additives, Because of the excellent "shear stability" with a very strong anti-corrosion, oxidation and wear-ability, this four stroke oil is suitable for use in inboard engines as well in high speed and heavy duty engines such as outboard engines of Mercury. This engine oil meets the latest requirements set by the NMMA. The specific marine oil is not suitable for use in outboard exhaust aftertreatment systems and for use in cars.

According to the specifications of

MerCruiser
Mercury
NMMA FC-W

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL022001	1 L	6	450
BL022005	5 L	4	112
BL022020	20 L	1	30
BL022060	60 L	1	6
BL022205	205 L	1	2
BL022999	1000 L	1	-
PBL022000	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.855	kg/l
Viscosity SAE	25W-40 25W-40	
Kinematic Viscosity at 40°C	151.9	mm ² /s
Kinematic Viscosity at 100°C	15.5	mm ² /s
Viscosity Index	104	
Flashpoint COC	244	°C
Pourpoint	-21	°C
Total Base Number	7.7	mgKOH/g

These characteristics are typical of current production. Variations in these characteristics may occur.