



37000 UTTO GL-4 Mineral

Document version: May 18, 2024



Description

This mineral GL-4 UTTO (Universal Tractor Transmission Oil) transmission oil has been specially developed for tractors that need one lubrication oil for the hydraulic system, drive, differential, wet brakes and clutches.

According to the specifications of

API GL-4
Allison C4
CASE IH MS 1206 / MS 1207 / MS 1210
CASE New Holland MAT 3505 / 3525
Ford New Holland FNHA-2-C-201.00 / M2C134-C / M2C134-D
John Deere J20C / J20D
Massey Ferguson M-1135 / M-1143 / M-1145
Volvo Construction Equipment WB-101
ZF TE-ML 03E / 05F / 17E / 21F

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
37001	1 L	6	450
37005	5 L	4	112
37020	20 L	1	30
37060	60 L	1	6
37205	205 L	1	2
37999	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.885	kg/l	
Viscosity SAE	10W-30 10		
Kinematic Viscosity at 40°C	58.5	mm ² /s	
Kinematic Viscosity at 100°C	10	mm ² /s	
Viscosity Index	158		
Dynamic Viscosity at -20°C	2900	mPa.s	
Flashpoint COC	212	°C	
Pourpoint	-39	°C	
Total Base Number	7.5	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.