



04000A Motor Oil 10W-40 Super High Performance Diesel Truck

Document version: Apr 27, 2024



Description

This high-grade semi synthetic motor oil has been specially developed for diesel engines of commercial vehicles. In addition this motor oil has been formulated to make long oil-change intervals possible and to prevent bore polishing.

According to the specifications of

ACEA B3 / B4 / E7
API CF-4 / CG-4 / CH-4 / CI-4
Allison C4
Cummins CES 20076 / CES 20077 / CES 20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
MAN M 3275
MB 228.3
MTU Type 2
Mack EO-M Plus / EO-N
Renault RLD / RLD-2
Volvo VDS-3

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04020A	20 L	1	30
04060A	60 L	1	6
04205A	205 L	1	2
04999A	1000 L	1	-
P04000A	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.867	kg/l	
Viscosity	10W-40		
Kinematic Viscosity at 40°C	86	mm ² /s	
Kinematic Viscosity at 100°C	13.1	mm ² /s	
Viscosity Index	153		
Dynamic Viscosity at -25°C	5900	mPa.s	
Flashpoint COC	243	°C	
Pourpoint	-42	°C	
Total Base Number	11.9	mgKOH/g	
Sulphated Ash	1.9	mass%	

These characteristics are typical of current production. Variations in these characteristics may occur.