



## 37000 UTTO GL-4 Mineral

Document version: Apr 22, 2024



### Description

This mineral GL-4 UTTO (Universal Tractor Transmission Oil) transmission oil has been specially developed for tractors that need one lubrication oil for the hydraulic system, drive, differential, wet brakes and clutches.

### According to the specifications of

API GL-4  
Allison C4  
CASE IH MS 1206 / MS 1207 / MS 1210  
CASE New Holland MAT 3505 / 3525  
Ford New Holland FNHA-2-C-201.00 / M2C134-C / M2C134-D  
John Deere J20C / J20D  
Massey Ferguson M-1135 / M-1143 / M-1145  
Volvo Construction Equipment WB-101  
ZF TE-ML 03E / 05F / 17E / 21F

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
37001	1 L	6	450
37005	5 L	4	112
37020	20 L	1	30
37060	60 L	1	6
37205	205 L	1	2
37999	1000 L	1	-

## Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.885	kg/l	
Viscosity SAE	10W-30 10		
Kinematic Viscosity at 40°C	58.5	mm <sup>2</sup> /s	
Kinematic Viscosity at 100°C	10	mm <sup>2</sup> /s	
Viscosity Index	158		
Dynamic Viscosity at -20°C	2900	mPa.s	
Flashpoint COC	212	°C	
Pourpoint	-39	°C	
Total Base Number	7.5	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.