



## 53000 2-Stroke Gear Oil 10W-40 Semi Synthetic

Document version: Apr 22, 2024



### Description

MPM 2-Stroke Gear Oil 10W-40 Semi Synthetic is specific suitable into the gearboxes from air- and water-cooled 2-stroke motorcycles. This gear oil gives a high-performance protection under heavy conditions. The special formulation ensures cleaning and is suitable for gearboxes with or without wet plate clutches.

### According to the specifications of

API SG / SH / SJ / SL / SM / SN  
JASO MA / MA2

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
53001	1 L	6	450
53020	20 L	1	30
53060	60 L	1	6
53205	205 L	1	2
53999	1000 L	1	-

### Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.854	kg/l
Colour	Red	
Viscosity	10W-40	
Kinematic Viscosity at 40°C	95	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	14.9	mm <sup>2</sup> /s
Viscosity Index	165	
Pourpoint	-45	°C
Total Base Number	7.3	mgKOH/g

These characteristics are typical of current production. Variations in these characteristics may occur.