



## 54000 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic

Document version: Oct 18, 2019



### Description

This semi synthetic 4-stroke motorcycle oil SAE 10W-40 has been developed for air- and water-cooled 4-stroke motorcycle engines. This special motorcycle oil can be used all year round. This motor oil is suitable for the lubrication of gearboxes and in oil immersed clutches.

### Complies to the specifications of

API SL  
JASO MA / MA2

### Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 54001    | 1 L    | 6              | 450              |
| 54004    | 4 L    | 4              | 112              |
| 54020    | 20 L   | 1              | 30               |
| 54060    | 60 L   | 1              | 12               |
| 54205    | 205 L  | 1              | 2                |
| 54999    | 1000 L | 1              | -                |
| P54000   | 1 L    | 1              | -                |

| TEST                         | VALUE  |                    |
|------------------------------|--------|--------------------|
| Viscosity                    | 10W-40 |                    |
| Density at 15°C              | 0.876  | kg/l               |
| Kinematic Viscosity at 40°C  | 91     | mm <sup>2</sup> /s |
| Kinematic Viscosity at 100°C | 14.1   | mm <sup>2</sup> /s |
| Viscosity Index              | 160    |                    |
| Dynamic Viscosity at -25°C   | 5600   | mPa.s              |
| Flashpoint COC               | 224    | °C                 |
| Pourpoint                    | -39    | °C                 |
| Total Base Number            | 6.6    | mgKOH/g            |

These characteristics are typical of current production. Variations in these characteristics may occur.