



05000BM Motor Oil 5W-30 Premium Synthetic BMW / MB

Document version: May 20, 2024



Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes-Benz engines (incl. Mini) and among others. This motor oil meets the requirements laid down by BMW Long Life-01 and Mercedes-Benz 229.5. This motor oil is also suitable for petrol, LPG and diesel engines in cars and light commercial vehicles for which the ACEA A3/B4 specifications are demanded.

According to the specifications of

ACEA A3/B4
API CF / SL
BMW LL-01
MB 229.5
VW 502.00 / 505.00

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001BM	1 L	6	450
05005BM	5 L	4	112
05020BM	20 L	1	30
05060BM	60 L	1	6
05205BM	205 L	1	2
05999BM	1000 L	1	-
P05000BM	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.855	kg/l	
Viscosity	5W-30		
Kinematic Viscosity at 40°C	66.6	mm ² /s	
Kinematic Viscosity at 100°C	12.3	mm ² /s	
Viscosity Index	186		
Dynamic Viscosity at -30°C	5820	mPa.s	
Flashpoint COC	228	°C	
Pourpoint	-36	°C	
Total Base Number	10.8	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.