



01000B Motor Oil 20W-50 Multi Grade Classic

Document version: May 18, 2024



Description

This mineral motor oil has been specially developed for engines of classic cars constructed before 1980.

According to the specifications of

API CD / SF / SG
CCMC D1
CCMC G2
Ford M2C9011-A
GM 6085M
MIL-L-46152B

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 01001B | 1 L | 6 | 450 |
| 01004B | 4 L | 4 | 112 |
| 01005B | 5 L | 4 | 112 |
| 01020B | 20 L | 1 | 30 |
| 01060B | 60 L | 1 | 6 |
| 01205B | 205 L | 1 | 2 |
| 01999B | 1000 L | 1 | - |
| P01000B | 1 L | 1 | - |

Standard analyses

| TEST | VALUE | | METHOD |
|------------------------------|--------|--------------------|------------|
| Density at 15°C | 0.880 | kg/l | ASTM D4052 |
| Viscosity | 20W-50 | | SAE |
| Kinematic Viscosity at 40°C | 166 | mm ² /s | ASTM D445 |
| Kinematic Viscosity at 100°C | 18.1 | mm ² /s | ASTM D445 |
| Viscosity Index | 121 | | ASTM D2270 |
| Dynamic Viscosity at -15°C | 8500 | mPa.s | ASTM D5293 |
| Flashpoint COC | 235 | °C | ASTM D92 |
| Pourpoint | -24 | °C | ASTM D6892 |
| Total Base Number | 5.5 | mgKOH/g | ASTM D2896 |
| Sulphated Ash | 0.6 | mass% | ASTM D874 |

These characteristics are typical of current production. Variations in these characteristics may occur.