



32000BG Hydraulic Oil HLP 32

Document version: May 20, 2024

Description

This mineral multi-functional hydraulic oil has a very broad application scope, and is suitable for use in a wide range of hydraulic and industrial equipment. The blend additive package in this MPM hydraulic oil aids in reducing corrosion, foaming and ensures wear is kept to a minimum.

According to the specifications of

DIN 51524 Part 2 HLP

Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 32005BG | 5 L | 4 | 112 |
| 32020BG | 20 L | 1 | 30 |
| 32060BG | 60 L | 1 | 6 |
| 32205BG | 205 L | 1 | 2 |
| 32999BG | 1000 L | 1 | - |

Standard analyses

| TEST | VALUE | METHOD |
|------------------------------|-----------|--------------------|
| Density at 15°C | 0.872 | kg/l |
| Viscosity | ISO VG 32 | |
| Kinematic Viscosity at 40°C | 31.4 | mm ² /s |
| Kinematic Viscosity at 100°C | 5.4 | mm ² /s |
| Viscosity Index | 106 | |
| Flashpoint COC | 207 | °C |
| Pourpoint Typical | -33 | °C |
| FZG A/8.3/90 | 12 | level |

These characteristics are typical of current production. Variations in these characteristics may occur.